




# KND-1-NS002D-R2

## KLD-1-NS



1. 滑动开关型号 SLIDE SWITCH MODEL: KND-1-NS002D-R2
2. 焊线端子 SOLDER CONNECTOR TYPE:  
单刀四掷, 多回路 SINGLE POLE FOUR THROW, MULTI-CIRCUIT
3. 额定值 RATING: ▲ 10A 250VAC  $\mu$  T85   
▲ 10(2)A 250VAC  $\mu$  T85   
7(2)A 250VAC  $\mu$  T85
4. 接触电阻 CONTACT RESISTANCE: <math>< 50\text{m}\Omega</math> (INITIAL)
5. 绝缘电阻 INSULATION RESISTANCE:  $\geq 100\text{M}\Omega$  (DC500V/1MIN)
6. 介电强度 DIELECTRIC STRENGTH: 1500V /0.5mA /1MIN
7. 机械寿命 MECHANICAL LIFE: >100000 CYCLES
8. 电气寿命 ELECTRICAL LIFE: >100000 CYCLES
9. 端子手工焊接条件 SOLDER ABILITY OF TERMINAL: MAX350°C, 3S
10. 操作力 OPERATION FORCE: 600 $\pm$ 200gf
11. 所有部件均使用环保材料 ALL MATERIALS ARE RoHS COMPLIANT

线路图  
CIRCUIT DIAGRAM



电流电路  
CURRENT CIRCUIT  
CIRCUIT:002D

位置 POSITION	电路
1(INITIAL) 起始	OFF
2	C2+2
3	C1+1, C2+2+3
4	C2+3

